



50

together @ VINCI



corrugated pipes



ACCESSORIES FOR CORRUGATED PIPES



GASKET

Ø mm	110	160	200	250	300	350	400



COUPLER - 2 joints for each coupler

Ø mm	110	160	200	250	300	350	400



MALE CAP


Ø mm	110	160	200	250	300	350	400



FE MALE CAP - 1 joint

Ø mm	110	160	200	250	300	350	400

FORMED CORRUGATED FITTINGS M/M



30° BEND

Ø mm	110	160	200	250	300	350	400



45° BEND

Ø mm	110	160	200	250	300	350	400



60° BEND

Ø mm	110	160	200	250	300	350	400



90° BEND


Ø mm	110	160	200	250	300	350	400

FORMED CORRUGATED FITTINGS M/M



90° TEE

Ø mm	110	160	200	250	300	350	400
------	-----	-----	-----	-----	-----	-----	-----




90° REDUCING TEE

Ø mm	160	200	250	300	350	400
D1 min	110	110	110	110	110	110
D1 max	110	160	200	250	300	350



45° Y

Ø mm	110	160	200	250	300	350	400
------	-----	-----	-----	-----	-----	-----	-----




45° REDUCING Y

Ø mm	160	200	250	300	350	400
D1 min	110	110	110	110	110	110
D1 max	110	160	200	250	300	350



ECCENTRIC INCREASE M/M

Ø mm	160	200	250	300	350	400
D1 min	110	110	110	110	110	110
D1 max	110	160	200	250	300	350



ECCENTRIC INCREASE F/F

Ø mm	160	200	250	300	350	400
D1 min	110	110	110	110	110	110
D1 max	110	160	200	250	300	350



